Patient Cables and Lead Wires Directions for use

Patient cables and electrode lead wires are used to connect electrodes, catheters, and/or sensors placed at appropriate sites on the patient to a monitoring device for general monitoring and/or diagnostic evaluation by a healthcare professional. Be sure to read and follow all of the instructions that come with the OEM monitor. Patient cables and lead wires meet the requirements of the ANSI/AAMI standard for patient cables and lead wires (ANSI/AAMI EC53-1995).

In accordance with 21 CFR 898 and IEC 60601-1 subclause 56.3, patient cables and lead wires are constructed and tested in such a manner as to preclude patient contact with hazardous voltages.

Cleaning: patient cables and lead wires can be cleaned at least 15 times with the following: green soap, green soap tincture (US Pharmacopeia) or alcohol free hand soap, 2% glutaraldehyde solution (such as cidex), sodium hypochlorite (bleach) solution 10% in water. To clean:

1. Disconnect the patient cable and/or lead wire from the monitoring device.

△CAUTION
When disconnecting, pull on the plug itself, not on the cable.

- 2. Dampen a clean cloth or gauze pad with an appropriate cleaning solution and wipe all exposed surfaces.
- Dampen a clean cloth or gauze pad with sterile or distilled water and again wipe all exposed surfaces.
- 4. Dry all exposed surfaces with a clean, and dry cloth or gauze pad.

△CAUTION
Never immerse patient cables or lead wires in any liquid.
△CAUTION
Do not sterilize patient cables or lead wires by autoclave, radiation, or steam.

Note: patient cables and electrode lead wires do not contain natural rubber or latex. Caution: Federal (U.S.) Law restricts this device to use by or on the order of a physician.







STERILE



10°C







Do not immers



Do not autoclave